

full line

# pH ELECTRODE

Model : PE-03, PE-11, PE-01

ISO-9001, CE, IEC1010

PE-06HD, PE-04HD, PE-03K7, PE-05T, PE-21



PE-11



PE-03



PE-01



PE-06HD



PE-05T



PE-03K7



PE-21



PE-04HD



Laboratory Equipment Manufacturer

[www.mrclab.com](http://www.mrclab.com)



**full line**

# **pH ELECTRODE**

pH ELECTRODE Model : PE-03	<ul style="list-style-type: none"><li>* General purpose, laboratory and field usage.</li><li>* 12.3 mm dia. x 160 mm.</li><li>* Epoxy body, 1 - 13 pH.</li></ul>
pH ELECTRODE Model : PE-11	<ul style="list-style-type: none"><li>* General purpose, laboratory and field usage.</li><li>* 10 mm dia. x 130 mm.</li><li>* Epoxy body.</li><li>* 1 - 13 pH. (0 - 14 pH typical)</li></ul>
pH ELECTRODE Model : PE-01	<ul style="list-style-type: none"><li>* Professional, laboratory and field usage.</li><li>* 9.5 mm dia. x 130 mm.</li><li>* Epoxy body.</li><li>* 0 - 14 pH.</li></ul>
SPEAR TIP pH ELECTRODE  Model : PE-06HD PE-04HD	<ul style="list-style-type: none"><li>* The "Spear Tip pH electrode" is perfect for those pH measurements in applications where sample piercing is required. Meat, sausage and cheese are ideal applications. The electrode features a very durable glass measuring spear packaged in a rugged virtually unbreakable epoxy body.</li><li>* Range : 0 to 14 pH (PE-04HD)</li><li>* Range : 1 to 13 pH (PE-06HD)</li></ul>
pH ELECTRODE + Temp. PROBE ( combination kit of pH electrode )  Model : PE-03K7	<ul style="list-style-type: none"><li>* One kit combine of pH electrode PE-03 and Temp. probe TP-07 as a whole unit.</li><li>* Easy operation for the pH measurement under the ATC ( Automatic Temp. Compensation ).</li><li>* Available for PH-208, PH-207, PH-207HA, PH-221, PH-221E, YK-2005WA., PH-230SD. WA-2017SD, WA-2015, BPH-231.</li></ul>
pH electrode build in Temp. thermister inside.  Model : PE-05T	<ul style="list-style-type: none"><li>* pH electrode build in Temp. thermister inside.</li><li>* pH meter when make the temperature compensation, the extra optional Temp. probe is not necessary.</li><li>* Available for PH-208, PH-207, PH-207HA, PH-221, PH-221E, YK-2005WA., PH-230SD. WA-2017SD, WA-2015, BPH-231.</li><li>* General purpose, laboratory &amp; field usage. 1 to 13 pH ( typical 0 to 14 pH ).</li><li>* pH Operation Temp. : 5 to 60 °C ( 41 to 140 °F ).</li><li>* Temp. Probe Range : 0 to 60 °C ( 32 to 140 °F ).</li><li>* Epoxy Body Material.</li><li>* Connector : BNC plug for pH, ear phone plug for Temp.</li></ul>

\* Appearance and specifications listed in this brochure are subject to change without notice.

MRC.11.20